

# WATTYL FORESTWOOD OUTDOOR FURNITURE OIL (COLOUR RANGE)

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 3-Mar-2009  
C9317EC

CHEMWATCH Interim  
Version No:JRF

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

WATTYL FORESTWOOD OUTDOOR FURNITURE OIL (COLOUR RANGE)

### SYNONYMS

"Manufacturer's code: 11226 line"

### PROPER SHIPPING NAME

PAINT

### PRODUCT USE

■ Used according to manufacturer's directions.

### SUPPLIER

Company: WattyI Pty Ltd  
Address:  
4 Steel Street  
Blacktown  
NSW, 2148  
Australia  
Telephone: +61 2 9621 6255  
Emergency Tel: 1800 039 008  
Fax: +61 2 9831 4244  
Email: wattyI@wattyI.com.au

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.**

### RISK

Risk Codes Risk Phrases

R10 • Flammable.

R38 • Irritating to skin.

R43 • May cause SENSITISATION by skin contact.

R52/53 • Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 • HARMFUL- May cause lung damage if swallowed.

R67 • Vapours may cause drowsiness and dizziness.

### SAFETY

Safety Codes Safety Phrases

S36 • Wear suitable protective clothing.

S401 • To clean the floor and all objects contaminated by this material, use water and detergent.

S13 • Keep away from food, drink and animal feeding stuffs.

S46 • If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

S60 • This material and its container must be disposed of as hazardous waste.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
solvent		30-60
drying oil		10-20
gum turpentine	9005-90-7	1-10
other ingredients not contributing to the classification		balance

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

### EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

### NOTES TO PHYSICIAN

- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.
- For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:
- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients

with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.

- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
  - A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Treat symptomatically.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

### FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), acrolein, other pyrolysis products typical of burning organic material.

### FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

### HAZCHEM

·3Y

### Personal Protective Equipment

Breathing apparatus.  
Gas tight chemical resistant suit.  
Limit exposure duration to 1 BA set 30 mins.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.

### MAJOR SPILLS

■ CARE: Absorbent materials wetted with occluded oil must be moistened with water as they may auto-oxidize, become self heating and ignite.

Some oils slowly oxidise when spread in a film and oil on cloths, mops, absorbents may autoxidise and generate heat, smoulder, ignite and burn. In the workplace oily rags should be collected and immersed in water.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

---

## Section 7 - HANDLING AND STORAGE

---

### PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<= 1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

### SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C).

### STORAGE INCOMPATIBILITY

#### ■ HAZARD:

- Although anti-oxidants may be present, in the original formulation, these may deplete over time as they come into contact with air.
- Rags wet / soaked with unsaturated hydrocarbons / drying oils may auto-oxidise; generate heat and, in-time, smoulder and ignite. This is especially the case where oil-soaked materials are folded, bunched, compressed, or piled together - this allows the heat to accumulate or even accelerate the reaction
- Oily cleaning rags should be collected regularly and immersed in water, or spread to dry in safe-place away from direct sunlight or stored, immersed, in solvents in suitably closed containers.
- Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### EXPOSURE CONTROLS

Source	Material	TWA	TWA	Notes
--------	----------	-----	-----	-------

		ppm	mg/m <sup>3</sup>	
Australia Exposure Standards	WATTYL FORESTWOOD OUTDOOR Furniture Oil (Manufacturers Colour Range) (Petrol (gasoline)) gum turpentine (Turpentine (wood))		900	(see Chapter 16)
Australia Exposure Standards	gum turpentine (Turpentine (wood))	100	557	Sen

**PERSONAL PROTECTION****RESPIRATOR**

Type A- P Filter of sufficient capacity

**EYE**

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first- aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

**HANDS/FEET**

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

**NOTE:**

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch- bands should be removed and destroyed.
- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
  - frequency and duration of contact,
  - chemical resistance of glove material,
  - glove thickness and
  - dexterity.

**OTHER**

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight- weave non- static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

**ENGINEERING CONTROLS**

- For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion- resistant.

Air contaminants generated in the workplace possess varying " escape" velocities which, in turn, determine the " capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200-500 f/min.)

**Section 9 - PHYSICAL AND CHEMICAL PROPERTIES****APPEARANCE**

Coloured flammable liquid with a solvent odour; not miscible with water.

**PHYSICAL PROPERTIES**

Liquid.  
Does not mix with water.  
Floats on water.

State	Liquid	Molecular Weight	Not Available
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	145 - 200	Solubility in water (g/L)	Immiscible
Flash Point (°C)	31- 36	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	<1
Lower Explosive Limit	Not Available	Relative Vapour Density	>1

(%) Volatile Component (% vol)	Not Available	(air=1) Evaporation Rate	Not Available
State	Liquid	Molecular Weight	Not Available
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	145 - 200	Solubility in water (g/L)	Immiscible
Flash Point (°C)	31- 36	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	<1
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (% vol)	Not Available	Evaporation Rate	Not Available

### Section 10 - STABILITY AND REACTIVITY

#### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
  - Product is considered stable.
  - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.

### Section 11 - TOXICOLOGICAL INFORMATION

#### POTENTIAL HEALTH EFFECTS

##### ACUTE HEALTH EFFECTS

- Irritating to skin.
- HARMFUL-May cause lung damage if swallowed.
- Vapours may cause dizziness or suffocation.
- Vapours may cause drowsiness and dizziness.
- Inhalation and/or ingestion may produce health damage\*.
- May produce discomfort of the eyes and respiratory tract\*.
- \* (limited evidence).

##### CHRONIC HEALTH EFFECTS

- May cause SENSITISATION by skin contact.
- Possible respiratory sensitiser\*.
- Limited evidence of a carcinogenic effect\*.
- Cumulative effects may result following exposure\*.
- Repeated exposure potentially causes skin dryness and cracking\*.
- \* (limited evidence).

#### TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
  - d- Limonene is readily absorbed by inhalation and ingestion. Dermal absorption is reported to be lower than by the inhalation route.
  - Limonene exhibits low acute toxicity by all three routes in animals.
  - Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke' s oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.
- WATTYL FORESTWOOD OUTDOOR FURNITURE OIL (MANUFACTURERS COLOUR RANGE):

##### ■ for petroleum:

This product contains benzene which is known to cause acute myeloid leukaemia and n- hexane which has been shown to metabolize to compounds which are neuropathic. This product contains toluene.

This product contains ethyl benzene and naphthalene from which there is evidence of tumours in rodents  
Carcinogenicity: Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.

##### GUM TURPENTINE:

TOXICITY	IRRITATION
Oral (human) LDLo: 1748 mg/kg	Eye (human): 175 ppm
Unreported (man) LDLo: 441 mg/kg	
Oral (woman) TDLo: 560 mg/kg	
Oral (rat) LD50: 5760 mg/kg	
Inhalation (human) TClO: 175 ppm	

##### ■ For bicyclic terpenes:

Acute toxicity: The literature abounds with clinical reports of accidental and intentional acute poisoning with pinene- based turpentine.  
Rat oral LD50 values are available for alpha- pinene, beta- pinene, camphene and turpentine oil and indicate these materials to be very low in oral acute toxicity with LD50 values in the range from 3388 mg/kg to greater than 5000 mg/kg.  
Acute inhalation toxicity has been measure in different animal species.

### Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long- term adverse effects in the aquatic environment.  
This material and its container must be disposed of as hazardous waste.

### Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
  - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
  - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.  
A Hierarchy of Controls seems to be common - the user should investigate:
- Reduction.
  - DO NOT allow wash water from cleaning or process equipment to enter drains.

- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

---

### Section 14 - TRANSPORTATION INFORMATION

---

Labels Required: FLAMMABLE LIQUID

**HAZCHEM:**

•3Y (ADG7)

**ADG7:**

Class or Division:	3	Subsidiary Risk:	None
UN No.:	1263	Packing Group:	III
Special Provision:	163, 223	Limited Quantity:	5 L
Portable Tanks & Bulk Containers - Instruction:	T2	Portable Tanks & Bulk Containers - Special Provision:	TP1, TP29
Packagings & IBCs - Packing Instruction:	PP1	Packagings & IBCs - Special Packing Provision:	P001, IBC03, LP01

Name and Description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant [AUST.] entries)

**Land Transport UNDG:**

Class or division:	3	Subsidiary risk:	None
UN No.:	1263	UN packing group:	III

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)

**Air Transport IATA:**

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	III
Special provisions:	A3		

Shipping name: PAINT

**Maritime Transport IMDG:**

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F-E, S-E	Special provisions:	163 223 955
Limited Quantities:	5 L		

Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

---

### Section 15 - REGULATORY INFORMATION

---

POISONS SCHEDULE S5

**REGULATIONS****Regulations for ingredients**

**gum turpentine (CAS: 9005-90-7, 8006-64-2) is found on the following regulatory lists;**

"Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

**No data for WATTYL FORESTWOOD OUTDOOR Furniture Oil (Manufacturers Colour Range) (CW: JRF)**

---

### Section 16 - OTHER INFORMATION

---

**INGREDIENTS WITH MULTIPLE CAS NUMBERS**

Ingredient Name	CAS
gum turpentine	9005-90-7, 8006-64-2

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:  
[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

**This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.**

Issue Date: 3-Mar-2009

Print Date: 9-Jun-2011

This is the end of the MSDS.